

Valor VL 100



A UNIFIED PAYMENT SOLUTION

The Valor PayTech VL 100 is the first step to unifying your merchant's payment experience. Business owners can take advantage of the Valor PayTech system, combining their VL 100 with the Valor PayTech Virtual Terminal and Gateway with shopping cart integration. * Merchants can finally bring their entire business under one payments roof. The easy-to-use Valor VL 100 offers a full-color LCD touchscreen with EMV and NFC payment acceptance. Along other incredible features, such as SMS receipts, the Valor VL 100 is the new favorite of merchants and partners everywhere.

Not-So-Standard Standard Features

- Multiple connectivity options including Ethernet, WiFi and Dial-Up allow for any business to connect
- Auto-Connection Fallback allows for the device to reconnect via another connection option if one were to fail, keeping you always connected.
- Digital Signature options
- SMS Receipts allow businesses to go green
- EMV and NFC ready to take the most secure payments and prevent fraud
- PayLo Ready

For sales, please call:

Firstname Lastname



*Shopify and Magneto only, available only on Traditional

signapay.com

4100 W. Royal Lane, Suite 150 | Irving, TX 75063 | 800-944-1399

SignaPay is a registered ISO of Commercial Bank of California, Irvine, CA, Esquire Bank, Garden City, NY, Synovus Bank, Columbus, GA

© Copyright 2006 - 2021, All Rights Reserved, SignaPay, LTD. 2006.

SIGNAPAY
AUTHORIZED PARTNER

Processor		32-bit Secure Microprocessor running powerful Linux based OS	
Memory	Flash/DDRDRAM	128 MB/64MB (Up to 256MB/128MB)	
	Micro-SD Socket	Yes	
Display		3.5" Color TFT LCD 320 x 480 Pixels	
Touch Screen		Yes	
Card Reader	Magnetic Stripe	ISO 7810, 7811, 7813 Triple Track, Bi-Directional	
	Contact Card	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
		SAM Card	2 (Up to 4)
	Contact-less (Optional)	ISO 14443 Type A, B ISO 18092 NFC Mifare & Sony FeliCa Working Frequency 13.56 MHz	
	Dual SIM	Yes	
Communications Interface Options	Wire	Ethernet Dial-Up Modem RS232 * 2 USB * 2	
Indicators	LED - Contact-less	No	
	Audio Buzzer	Yes	
Keypad	Standard Keys	15	
	Function Keys	No	
Printer		57 mm x 50 mm, 100mm/sec	
Software		SDK KMS TMS GDB CTOS library ISO 8583 library Crypto library	
Crypto		TRNG DES T'DES AES RSA MK/SK DUKPT T'DES DUKPT	
Power Supply	Power Adapter	DC 9V/4A	
	Battery	Li-Polymer 7.4-8.2V 1150mAh 5000mA (Max discharge current)	
Dimensions		190(L) x 78(W) x 78(H)	
Weight		350 g	
Environment	Operating Temperature	0°C to 50°C	
	Storage Temperature	-20°C to 70°C	
	Operating Humidity	5% to 90% non-condensing	
	Storage Humidity	5% to 90% non-condensing	
Certification		PCI PTS 4.x EMV L1/L2 payWave PayPass ExperssPay D-PAS Interac Flash J-Speedy FeliCa UnionPay UICS TQM PBOC L1/L2	
Optional Additional Feature		Speaker Detachable Battery	