

PAX A80



Fast and Secure Credit Card Transactions

Powered by Android - The PAX A80 is the most cost-effective in the A-series is versatile enough to work as a countertop or indoor portable device (given the optional backup battery).

Leverage a world of Android-based apps to get more for your business, and always run at peak performance.

Full connectivity means the A80 is a reliable workhorse that will process payments safely and quickly, even during the busiest hours.

4-inch touchscreen display and multiple network connectivity, A80 delivers the best user experience to the modern consumers.

Effortless and Easy Features with Hi-Performance.

Unprecedented Security

- Ultra-safe security processor
- NFC contactless certified
- Supports RSA, AES, 3DES
- Micro SD expandability
- PCI PTS 5.x, SRED

Exceptional Performance

- Inbuilt 0.3 Megapixel front camera (optional)
- WiFi, Bluetooth, Dial, Ethernet
- PayDroid powered by Android 6.0
- Optional battery backup
- Capacitive touchscreen

For more information:





SPECIFICATIONS

OS	PayDroid Powered by Android 6.0
Processor	Application CPU: Quad-core Cortex-A53, 1.2GHz Security CPU: Cortex M3
Memory	1GB DDR + 8GB eMMC 1 x Micro SD Card Slot, Supports up to 32GB
Card Readers	Magnetic Card Reader Smart Card Reader Contactless Card Reader
Camera	0.3 Megapixel Fixed Focus Front Camera (optional) Reads 1D & 2D Codes
Display	4-Inch Colour Display 800 x 480 Pixels Capacitive Touchscreen
Audio	1 x Speaker
Physical Keypad	10 x Numeric Keys 5 x Function Keys Back-Lighting
Communications	WiFi (2.4G)(optional) Dial (PSTN) LAN Bluetooth 4.0 (optional)
Card Slots	3 x SAM 1 x SIM + 2 x SAM
Peripheral Ports	1 x HOST USB 2.0 1 x Micro USB 2.0, OTG 1 x PINpad 1 x RS232 1 x LAN 1 x Line 1 x Phone
Printer	High-Speed Thermal Printer Print Speed: 90mm/s Paper Width: 58mm Paper Diameter: 50mm
Battery	7.4V / 720mAh Rechargeable Li-ion Battery (optional)
Adapter	Input: 100 - 240V AC, 50Hz / 60Hz Output: 9.0V DC, 1.0A
Accessories	Cluster Cable (optional) Privacy PIN Shield (optional) Battery Backup (optional)
Physical	L x W x H (mm) : 181 x 84 x 81 Weight (g) : 405 (Excluding Battery)
Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature 10% ~ 93% Relative Humidity, Non-condensing -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature
Certifications	PCI PTS 5.x, SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless American ExpressPay Discover D-PAS IC MasterCard TQM Interac_Flash L2 J/Speedy L2 UL CE FCC RoHs